

## THE SURFACES:

	Nordic spruce	Nordic pine	Larch native	Siberian larch	Alpine pine	Oak European	European red oak	Ash European
Raw surfaces								
raw (fine sanded / partially touched up)	•	٠	٠	•	•			
raw (smoothed / fine sanded)						•	٠	٠
raw (fine sanded) & brushed	٠	٠	٠	•	•			
raw (smoothed / fine sanded) & brushed						•	٠	•
Naturally oiled surfaces	-							
2x natural oiled	٠	٠	٠	•	•	•	٠	٠
brushed & 2x natural oiled	•	•	•	•	•	•	٠	٠
2x matt oiled (raw effect)	٠	٠	٠	•	•	•	٠	٠
brushed & 2x matt oiled (raw effect)	٠	•	٠	•	•	•	٠	٠
2x white oiled	٠	٠	٠	٠		٠	٠	٠
brushed & 2x white oiled	•	•	•	•		•	٠	٠
2x precious smoke oiled (smoked effect)						•	٠	٠
gebürstet & schwarz gealtert, 2x natur geölt						•	٠	٠
SPECIAL SURFACE								
raw & band saw cut	•	•	٠	•	•	•	٠	٠
Band saw cut & 2x natural oiled	٠	•	٠	•	•	•	٠	٠
Band saw cut & 2x noble matt oiled (raw effect)	٠	٠	٠	٠	•	•	٠	٠
BaBand saw cut & 2x white oiled	•	٠	٠	•		•	٠	٠
Band saw cut & 2x noble smoke oiled (smoked effect)						•	٠	٠
MATT LACQUERED*								
lacquered (6-layer / gloss level 10)	٠	•	٠	٠		•	٠	٠
brushed & lacquered (6-layer / gloss level 10)						٠	٠	٠

## TEST REPORT for oiled surfaces according to DIN 68861-1:2011-01

O Resistance test according to EN 12720

## **TEST REPORT for lacquered surfaces**

- O Abrasion stress in accordance with DIN EN 14354:2017 (Falling Sand)
- O Resistance test in accordance with EN 12720

- O DiPT Prüfbericht Nr. 50896-001
- O Cross-cut test in accordance with DIN EN ISO 2409:2013-06
- O Behaviour when scratched after DIN 68861-4