

BASEBOARDS

Type of wood	Surface	Profile A or B	
Spruce	oiled	A	
Pine	oiled	A	
Larch Canadian	oiled	A	B
Larch Canadian	white oiled		B
Larch Canadian	noble matt oiled		B
Larch European	oiled	A	
Oak	oiled	A	B
Oak	whiteoiled		B
Oak	noble matt oiled		B
Oak	noble smoke oiled		B
Oak	brushed, aged, black, oiled		B
Ash	oiled	A	

Profile A
20 x 55 mm






Profile B
20 x 60 mm



Other finishes available on request

INSTALLATION

FLOOR CLIPS	Cover width: 135 mm Requirement per m ² : 15 pcs. Deck width: 137 mm	
FLOOR GLUE	SIKABOND® GLUE 54 Requirement ca. 700 - 1300 g/m ² 13 kg per bucket Fast setting, solvent-free, elastic 1-component PU glue for wood floors	
PRIMER	SIKA PRIMER MR. FAST Requirement ca. 190 - 250 g/m ² 4,2 kg per package Water-based, solvent-free primer and moisture barrier for gluing wood flooring with SikaBond® adhesives on difficult subfloors	
LAYING MATERIAL	SCREWS 3,5 X 50 MM Requirement ca. 25 pcs./m ² 500 Piece per package	