

THE SURFACES:

	Spruce nordic	Pine nordic	Larch european	Larch canadian	Pine alpine	Oak european	Red oak european	Ash european
SANDED								
sanded & 2x natural oiled	•	•	•	•	•	•	•	•
sanded & 2x white oiled	•	•	•	•		•	•	•
sanded & 2x noble matt oiled (raw effect)	•	•	•	•	•	•	•	•
sanded & 2x noble smoke oiled (smoked effect)						•	•	•
sanded & lacquered (6-layer / gloss level 10)*	•	•	•	•		•	•	•
BRUSHED								
brushed & 2x natural oiled	•	•	•	•	•	•	•	•
brushed & 2x white oiled	•	•	•	•		•	•	•
brushed & 2x noble matt oiled (raw effect)	•	•	•	•	•	•	•	•
brushed & aged black, 2x natural oiled						•	•	•
brushed & lacquered (6-layer / gloss level 10)*						•	•	•
BAND SAW CUT								
band saw cut & 2x natural oiled	•	•	•	•	•	•	•	•
band saw cut & 2x white oiled	•	•	•	•		•	•	•
band saw cut & 2x noble matt oiled (raw effect)	•	•	•	•	•	•	•	•
band saw cut & 2x noble smoke oiled (smoked effect)						•	•	•
RAW SURFACES								
raw & band saw cut	•	•	•	•	•	•	•	•
raw (fine sanded / partially touched up)	•	•	•	•	•			
raw (smoothed / fine sanded)						•	•	•
raw (fine sanded) & brushed	•	•	•	•	•			
raw (smoothed / fine sanded) & brushed						•	•	•

TEST REPORT for oiled surfaces according to DIN 68861-1:2011-01

- Resistance test according to EN 12720
- DiPT Prüfbericht Nr. 50896-001

TEST REPORT for lacquered surfaces

- Cross-cut test in accordance with DIN EN ISO 2409:2013-06
- Behaviour when scratched after DIN 68861-4
- Abrasion stress in accordance with DIN EN 14354:2017 (Falling Sand)
- Resistance test in accordance with EN 12720

* soluble lacquer / UV cured